

The A-series of AMS aluminium high-voltage electric fencing protected link is utilized as a lead-out link from your energizer to the fence what's more, for any remaining protected high-voltage transmissions. It is utilized with a range of aluminium wires and galvanized earth spikes. Accessible in single-core or three-centre choices.



## FEATURES

- It's an Ideal AMS cable when the aluminium wire is utilized
- Low electrical resistance reduces power and voltage drops over long distances
- The 3-centre A-Series reduces installation time
- 30m 3 centre cables are reasonable for Wizord 2, Wizord 4, Merlin 4i, Eagle 13LCD, Eagle 15LCD, Eagle 18LCD, Eagle 25LCD and Eagle 28LCD energizers
- 100m 3 centre cables are reasonable for Wizord 2, Wizord 4, Merlin 4i, Eagle 13LCD, Eagle 15LCD and Eagle 18LCD energizers
- The Max distance of 3 core cables is reasonable for Merlin M18S and Merlin M28S is 15m



## SPECIFICATIONS

Conductors	3 core HT cable 1.6mm stranded inner conductors Single core HT cable 1.6mm solid inner conductor
Material	Aluminium UV stabilised double insulated cable
Roll size	30m,100m,200m,500m,1000m
Colour	Black
Type	3 Core Stranded Core Solid Single Core

STOCK CODE	DESCRIPTION
AM-3AS030-4	3 core Aluminium HT Cable (A-series) 30m
AM-3AS100-4	3 core Aluminium HT Cable (A-series) 100m
AM-AS100-4	Solid Aluminium HT Cable (A-series) 100m
AM-AS200-4	Solid Aluminium HT Cable (A-series) 200m
AM-AS500-4	Solid Aluminium HT Cable (A-series) 500m
AM-AS1000-4	Solid Aluminium HT Cable (A-series) 1000m

**02 YEARS WARRANTY**

