



AMS Ferrules are utilized to join the conductive electrified barrier wires forever. This is a high-security wire association since it can't be taken out.



AVAILABLE IN

Aluminium:

- 6mm is utilized with the 1.6mm aluminium wire
- 10mm is utilized with the 2.0mm and 2.5mm aluminium wire

304 Stainless Steel:

- 6mm is utilized with 1.0mm and 1.2mm treated steel wires
- 10mm is utilized with 1.6mm and 2.0mm treated steel wires

Tinned Copper:

- 6mm is utilized with the stirred

STOCK CODE	DESCRIPTION
AM-F6AFT-1	6mm Aluminium Ferrules (bag of 100)
AM-F6S-1	6mm Tinned Copper Ferrules (bag of 100)
AM-F6S/SS-1	6mm 304 Stainless Steel Ferrules (bag of 50)
AM-F10AFT-1	10mm Aluminium Ferrules (bag of 100)
AM-F10-1	10mm Tinned Copper Ferrules (bag of 100)
AM-F10S/SS-1	10mm 304 Stainless Steel Ferrules (bag of 50)
AM-F16-1	16mm Tinned Copper Ferrules (bag of 100)



SPECIFICATIONS

Material	Aluminium, Stainless Steel, Tinned Copper
Diameter	6mm, 10mm, 16mm
Packaging	50 Pack, 100 Pack

02 YEARS WARRANTY

